









Do more in less time—fast setup, printing, sharing

- Get the job done quickly without sacrificing quality thanks to this printer's fast (Economode) print setting—2 D/A1-sized prints per minute.
- Experience continuous printing with reliable HP 300-ml matte black ink cartridges, a convenient front-loading top roll, and media length tracking.
- Save time and paper with 2 online rolls with smart switching.
- Print batch HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, PowerPoint) files easily—without opening any application—thanks to the free HP Instant Printing Utility and the embedded Web server.
- Medium-sized teams can easily share this printer thanks to its built-in network card.

Small details increase your power to communicate

- Achieve rich, dark blacks and fine detailed lines with HP Vivera inks, including 2 HP Vivera blacks and a gray ink in this 6-ink printing system.
- Produce exacting detail with 0.0008 inch (0.02 mm) minimum line width,⁽² and highly accurate drawings with 0.1% line accuracy.
- Easily create stunning large-format posters that convey your message loud and clear with the optional Serif PosterDesigner Pro for HP.⁽³⁾
- Transform your everyday printing with 2 HP media innovations—new and improved HP

bond papers with ColorPRO Technology and HP Recycled Bond Paper, made of 100% recycled base paper.

 Optimize blueprints—use this printer's new printing mode for generic natural tracing paper.

Print confidently with a reliable, secure solution

- A busy network is not a problem anymore thanks to 32 GB of memory for file processing and reliable In-printer processing architecture.
- Secure connectivity with built-in Gigabit Ethernet networking and secure IPsec and IPv6. A Linux PS driver offers additional support for Linux users.⁽⁴⁾
- Trusted security—use advanced access controls via the embedded Web server; secure disk erase and the external hard disk accessory⁽⁵ provide even more security.
- Do more with your printer with PostScript capabilities.⁽⁴ And experience greater operating system support with original HP-GL/2 and RTL.
- Manage your printer fleet and costs with HP Web Jetadmin, embedded Web server and the HP accounting tool.

vivera

and highly ne accuracy. at posters that clear with the of or HP.⁽³⁾ mg with 2 HP mproved HP Commence and the state of th



-) Improve your productivity with automatic switching among 2 rolls.
- 2) HP-GL/2 addressable
- 3) Serif PosterDesigner Pro for HP is an optional software accessory to be purchased separately.

Adobe[®] PostScript[®] 3[®]

- 4) Available on the HP Designjet T1200 PostScript Version Printer only. Support in English.
- 5) The 160 GB external hard disk drive accessory is an optional accessory to be purchased separately. This accessory is intended to replace the printer's internal hard disk as the repository of personal data, and can be removed from the printer and stored in a secure place.

HP DESIGNJET T1200

PRINTER SERIES

TECHNICAL SPECIFICATIONS

Line drawings ¹²	Fast: 28 sec/page on D/A1, 103 D/A1 prints per hour
Color images	Fost: 549 ft²/hr (51 m²/hr) ^a Best: 33.3 ft²/hr (3.1 m²/hr) ^a
Printing	
Print resolution	Up to 2400 x 1200 optimized dpi
Margins	Roll: 0.2 x 0.2 x 0.2 x 0.2 in (5 x 5 x 5 x 5 mm) (borderless on photo papers)
(top x bottom x left x right)	Sheet: 0.2 x 0.67 x 0.2 x 0.2 in (5 x 16.75 x 5 x 5 mm)
Technology	HP Thermal Inkiet
Ink types	Dye-based (C, M, Y, G, PK); pigment-based (MK)
Ink colors	Cyan, gray, magenta, matte black, photo black, yellow
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
Ink cartridge size	300 ml (matte black) 130 ml (cyan, gray, magenta, matte black, photo black, yellow)
	69 ml (cyan, gray, magenta, photo black, yellow)
Printheads	3 (matte black and yellow, magenta and cyan, gray and photo black)
Line accuracy	+/- 0.1%/4
Minimum line width	0.0008 in (0.02 mm) (HP-GL/2 addressable)
Guaranteed minimum line width	0.0024 in (0.06 mm) (ISO/IEC 13660:2001(E)) ⁽⁵
Maximum print length	300 ft (91 m) (OS and application dependent)
Media	
Handling	Sheet feed; two automatic roll feeds; automatic roll switching; automatic cutter
Types	Bond and coated papers, technical papers, films, photographic papers, backlit
ACTOR A	materials, self-adhesive materials
Weight	60 to 328 g/m ²
Size	8.26 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) sheets
71 - 1	11 to 44 in (27.94 to 111.76 cm) rolls
Thickness	Up to 11.8 mil
Memory	
	32 GB dedicated file-processing memory, 160 GB hard disk?
Connectivity	
Interfaces (standard)	1 Gigabit Ethernet (1000Base-T) port, 1 Hi-Speed USB 2.0 certified port, 1 EIO
	Jetdirect accessory slot
Interfaces (optional)	HP Jetdirect EIO print servers
Print languages (standard)	Base model: HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
1	PostScript Version Printer: Adobe® PostScript® 3™, Adobe PDF 1.7, TIFF, JPEG,
	HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Drivers (included)	HP-GL/2, HP-RTL, PostScript [®] drivers for Windows [®] (optimized for AutoCAD 2000 and
	higher); HP PCL 3 GUI , PostScript th drivers for Mac OS X and Linux th ; support for Citrix
	XenApp and Citrix XenServer environments
Recommended system requireme	
Mac	Mac OS X v 10.4, Mac OS X v 10.5: PowerPC G4, G5, or Intel Core Processor;
Windows	GB RAM; 2 GB available hard disk space
vvindows	Windows XP* (SP2 or later): Intel* Pentium* family or AMD* K6/Athlon/Duron fam (1 GHz), 1 GB RAM, 2 GB available hard disk space; Windows Vista*: 32-bit (x86
	or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space
Dimensions (w x d x h)	To orbit the if processes (if one if a contrast of board and be a contrast of processes if
Printer	69.7 x 28.4 x 41.3 in (1770 x 722 x 1050 mm)
Shipping	75.98 x 30.16 x 30.7 in (1930 x 766 x 778 mm)
Weight	Trans a sear in frase a res arresting
Printer	189 lb (86 kg)
Shipping	253 lb (115 kg)
What's in the box	200 lo (10 kg)
WIDES IN THE DOX	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster,
1	start-up software, power cord
Environmental ranges	start-up software, power cord
Operating temperature	start-up software, power cord 41 to 104" F (5 to 40" C)
Operating temperature Recommended operating	start-up software, power cord
Operating temperature Recommended operating temperature	startup software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type)
Operating temperature Recommended operating temperature Storage temperature	startup software, power cord 41 to 104" F (5 to 40" C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C)
Operating temperature Recommended operating temperature Storage temperature Recommended operating	startup software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	startup software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type).
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity	startup software, power cord 41 to 104" F (5 to 40" C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic	start-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (-25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active	start-up software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby	start-up software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	start-up software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby	start-up software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, atomby Power consumption	startup software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type). 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, active Sound power, active Maximum	start-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (-25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, atomby Power consumption Maximum Powersave	stort-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, atomby Power consumption Maximum Powersove Off	start-up software, power cord 41 to 104" F (5 to 40° C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (-25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 waits < 7 waits (< 25 waits with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, atomby Power consumption Maximum Powersave	stort-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, atondby Power consumption Maximum Powersave Off Power requirements	start-up software, power cord 41 to 104" F (5 to 40° C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (-25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 waits < 7 waits (< 25 waits with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, atandby Power consumption Maximum Powersave Off	startup software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, atondby Power consumption Maximum Powersave Off Power requirements	startup software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts 120 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Power consumption Maximum Powersave Off Power requirements Certification	startup software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Power consumption Maximum Powersave Off Power requirements Certification	start-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersove Off Power requirements Certification Safety	startup software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexica (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Directive), Australia (ACMA), New Zeoland (RSM), China (CCC), Japa
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, stondby Sound pressure, stondby Sound power, active Sound power, atondby Power consumption Maximum Powersove Off Power requirements Certification Sofety	start-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Operating lemperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, stondby Sound pressure, stondby Sound power, active Sound power, active Maximum Powersave Off Power requirements Certification Sofety	startup software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexica (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Directive), Australia (ACMA), New Zeoland (RSM), China (CCC), Japa
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Cound pressure, stondby Sound pressure, stondby Sound power, active Sound power, active Sound power, stondby Power consumption Maximum Powersove Off Power requirements Certification Sofety Electromagnetic	startup software, power cord 41 to 104" F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type). 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japa (VCCI); Certified as Class A product: Korea (KCC)
Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic Environmental	stort-up software, power cord 41 to 104" F (5 to 40" C) 59 to 95" F (15 to 35" C) (depending on paper type) -13 to 131" F (25 to 55" C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts 12 valts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (INYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Diractive), Australia (ACMA), New Zealand (RSM), China (CCC), Japar (VCCI); Certified as Class A product: Koreo (KCC)

ORDERING	INFORMATION
Long the second s	

Product		
CH538A	HP Designjet T1200 44-in Printer	
CK834A	HP Designjet T1200 44-in PostScript Version Printer	
Accessories		
Q6709A	HP Designjet 44-inch Roll Feed Spindle	
CN501A	HP Designjet External Hard Disk	
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server	
CN088A	Serif PosterDesigner Pro for HP	
CN454A	SCP reprocontrol for HP (1 printer)	
CN455A	SCP reprocontrol for HP (2 printers)	
Original HP pri	intheads	
C9380A	HP 72 Gray and Photo Black Printhead	
C9383A	HP 72 Magenta and Cyan Printhead	
C9384A	HP 72 Matte Black and Yellow Printhead	
Original HP in		
C9397A	HP 72 69-ml Photo Black Ink Cartridge	
C9398A	HP 72 69-ml Cyan Ink Cartridge	
C9399A	HP 72 69-ml Magenta Ink Cartridge	
C9400A	HP 72 69-ml Yellow Ink Cartridge	
C9401A	HP 72 69-ml Gray Ink Cartridge	
C9403A	HP 72 130-ml Matte Black Ink Cartridge	
C9370A	HP 72 130-ml Photo Black Ink Cartridge	
C9371A	HP 72 130-ml Cyan Ink Cartridge	
C9372A	HP 72 130-ml Magenta Ink Cartridge	
C9373A	HP 72 130-ml Yellow Ink Cartridge	
C9374A	HP 72 130-ml Gray Ink Cartridge	
CH575A	HP 726 300-ml Matte Black Ink Cartridge	
	inting materials	
Q6627A	HP Super Heavyweight Plus Matte Paper 210 g/m ² , 36 in x 100 ft/914 mm x 30,5 m	
Q6628A	HP Super Heavyweight Plus Matte Paper 210 g/m ² , 42 in x 100 ft/1067 mm x 30,5 m	
C6030C	HP Heavyweight Coated Paper 130 g/m ² , 36 in x 100 ft/914 mm x 30,5 m	
C6569C	HP Heavyweight Coated Paper 130 g/m ² , 42 in x 100 ft/1067 mm x 30,5 m	
Q1956A	HP Heavyweight Coated Paper 130 g/m ² , 42 in x 225 ft/1067 mm x 67,5 m	
C6019B	HP Coated Paper 90 g/m ² , 24 in x 150 ft/610 mm x 45,7 m	
C6020B C6980A	HP Coated Paper 90 g/m ² , 36 in x 150 H/914 mm x 45,7 m	
C1860A	HP Coated Paper 90 g/m ² , 36 in x 300 ft/914 mm x 91,4 m HP Bright White Inkjet Paper 90 g/m ² , 24 in x 150 ft/610 mm x 45,7 m now with ColorPRO Technology	
C1861A	HP Bright White Inkjet Poper 90 g/m ² , 36 in x 150 ft/914 mm x 45,7 m now with ColorPRO Technology	
C6810A	HP Bright White Inkjet Paper 90 g/m ² , 36 in x 300 lt/914 mm x 91,4 m now with ColorPRO Technology	
Q1397A	HP Universal Bond Paper 80 g/m ² , 36 in x 150 ft/914 mm x 45,7 m now with ColorPRO Technology	
C3868A	HP Notural Tracing Paper 90 g/m ² , 36 in x 150 ft/914 mm x 45,7 m	
C3875A	HP Clear Film 174 g/m ² , 36 in x 75 ft/914 mm x 22,9 m	
51642B	HP Matte Film 160 g/m ² , 36 in x 125 ft/914 mm x 38,1 m	
Q1427A	HP Universal High-gloss Photo Paper 190 g/m ² , 36 in x 100 ft/914 mm x 30,5 m	
Q1421A	HP Universal Semi-gloss Photo Paper 190 g/m ² , 36 in x 100 ft/914 mm x 30,5 m	
CG459A	HP Premium Matte Photo Paper 210 g/m ² , 24 in x 100 ft/610 mm x 30,5 m	
CG460A	HP Premium Matte Photo Paper 210 g/m², 36 in x 100 ft/914 mm x 30,5 m	
C7960A	HP Reverse Print Matte Backlit Film 160 g/m², 36 in x 75 ft/914 mm x 22,9 m	
Q8834A	HP Self-adhesive Gloss Polypropylene 120 g/m², 36 in x 75 ft/914 mm x 22,9 m	
CG886A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 24 in x 100 ft/610 mm x 30,5 m	
CG887A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in x 100 ft/914 mm x 30,5 m	
CG888A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in x 100 ft/1067 mm x 30,5 m	
CG883A	HP Cockle-free Coated Paper 100 g/m², 24 in x 150 ft/610 mm x 45,7 m	
CG884A	HP Cockle-free Coated Paper 100 g/m², 36 in x 150 lt/914 mm x 45,7 m	
CG885A	HP Cockle-free Coated Paper 100 g/m ² , 42 in x 150 ft/1067 mm x 45,7 m	
CG889A	HP Recycled Bond Paper 80 g/m ² , 24 in x 150 ft/610 mm x 45,7 m made of 100% recycled base paper	
CG890A	HP Recycled Bond Paper 80 g/m², 36 in x 150 ft/914 mm x 45,7 m made of 100% recycled base paper	
CG891A	HP Recycled Bond Paper 80 g/m ² , 42 in x 150 ft/1067 mm x 45,7 m made of 100% recycled base paper	
HP Care Pack		
US237E	HP 3-year Next Business Day Onsite Support	
H4518E	HP Installation Services with Network Setup	
US234E	HP 3-year Next Business Day Onsite Support (9x5)	
US230E	HP 3-year Next Business Day Onsite Support (13x5)	
US236E	HP 4-year Next Business Day Onsite Support	
US235E	HP 5-year Next Business Day Onsite Support	

For more HP large-format printing materials and sizes please visit us online at; www.hp.com/go/designjet/supplies

Mechanical printing time
 Printed on plain media with Economode on
 Printed on glassy media
 +/-0.1% of the specified vector length or +/-0.1 mm (whichever greater) at 73° F (23° C), 50-60% relative humidity, on E/AD printing material in Best or Normal mode with HP Matte Film
 Measured on HP Matte Film
 Only supported through the HP Designjet T1200 44-in PostScript Version Printer
 384 MB RAM Memory

For additional information visit our website at: www.DirtDog.net 1-800-454-1310

FOR MORE INFORMATION, VISIT OUR WEBSITE AT WWW.HP.COM/GO/DESIGNJETT1200

Copyright 2009 Hewlett-Packard Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe PastCript 3 is a trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AMD is a trademark of Advanced Micro Devices, Inc. Intel and Pentium are trademarks of Intel Corporation in the U.S. and other countries. Windows, Windows XP, and Windows Vista are U.S. registered trademarks of Microsoft Corporation.

