

Xerox® WorkCentre® 5945/5955

Multifunction Printer

The WorkCentre 5945/5955 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



WorkCentre 5945 shown with Office Finisher



WorkCentre 5955 shown with Office Finisher with Booklet Maker



| System Specifications | WorkCentre 5945 | WorkCentre 5955 |
|--|---|--|
| Simplex Speed 8.5 x 11 in. / A4 (LEF) 8.5x13to8.5x14 in. /A4toB4 (SEF) 11x17 in. /A3 (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%) | 45 ppm 36 ppm 31 ppm | 55 ppm 36 ppm 31 ppm |
| Auto Duplex Speed 8.5x11 in. /A4 (LEF) 11x17 in. /A3 (SEF) | Up to 45 ipm / 2-sided 22.5 sheets per minute Up to 31 ipm / 2-sided 15.5 sheets per minute | Up to 55 ipm / 2-sided 27.5 sheets per minute Up to 31 ipm / 2-sided 15.5 sheets per minute |
| Monthly Duty Cycle¹ | Up to 175,000 pages | Up to 200,000 pages |
| Recommended Average Monthly Print Volume² | Up to 20,000 pages | |
| Hard Drive / Processor / Memory | Minimum 250 GB / 1 GHz Dual-core / 2 GB system | |
| Connectivity | 10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Optional Wi-Fi (with Xerox® USB Wireless Adapter) | |
| Controller Features | Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning | |
| Copy and Print | | |
| Copy and Print Resolution | Copy Up to 600 x 600 dpi; Print Up to 1200 x 1200 dpi, 256 shades of gray | |
| First-copy-out Time | As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder | |
| Page Description Languages | Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional) | |
| Print Features | Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring | |
| Mobile Printing | Apple® AirPrint™, Xerox® PrintBack, Xerox® Mobile Print (Optional), Xerox® Mobile Print Cloud® (Optional), Mopria™ certified, Xerox® Print Service (plug-in for Android™) | |
| Scan | | |
| Standard | Destinations: Scan to Mailbox; Scan to USB; Scan to Email; Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A | |
| Optional | Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® Professional, other solutions available through various Xerox Business Innovation Partners | |
| Fax | | |
| Standard Features | Internet Fax, Fax Build Job, Network Server Fax Enablement | |
| Optional Features | Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax, Fax Forward to Email or SMB, Walk-up Fax) | |
| Security | | |
| Standard Features | McAfee® Embedded, McAfee Policy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (undergoing evaluation), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions | |
| Optional Features | McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET) | |
| Accounting | | |
| Standard Features | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement | |
| Optional Features | Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox® Business Innovation Partners | |

Xerox® WorkCentre® 5945/5955

| Device Specifications | | | | |
|---|--|------------------------|---------------------|-----------------------|
| Control Panel Languages | US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan | | | |
| Accessories | | | | |
| Optional | Envelope Tray Kit (replaces Tray 2) Office Finisher Office Finisher with Booklet Maker Hole Punch for Office Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® (with USB Card Reader) Walk up Fax (One- or Two-line options, includes LAN Fax) ScanFlowStore® Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit | | | |
| Foreign Device Interface (FDI) (Optional) | Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers. | | | |
| Electrical Requirements | | | | |
| North America | Voltage : 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 15 A | | | |
| Europe | Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 10 A | | | |
| Power Consumption | WorkCentre 5945 | WorkCentre 5955 | | |
| Running (Average) | | | | |
| Base Unit with Offset Catch Tray: | 1,150 watts | | 1,250 watts | |
| Base Unit with Office Finisher: | 1,230 watts | | 1,330 watts | |
| Base Unit with Office Finisher with Booklet Maker: | 1,230 watts | | 1,330 watts | |
| Standby Mode | | | | |
| Base Unit with Offset Catch Tray: | 45 watts | | 45 watts | |
| Base Unit with Office Finisher: | 55 watts | | 55 watts | |
| Base Unit with Office Finisher with Booklet Maker: | 55 watts | | 55 watts | |
| Sleep mode | 3 watts | | | |
| Ready to Scan and Print (from Power On) | As fast as 230 seconds (3 minutes, 50 seconds) | | | |
| Recovery from Low Power | As fast as 4 seconds | | | |
| Recovery from Sleep | As fast as 28 seconds | | | |
| Operating Environment | | | | |
| Required Temperature Range | 50° to 90° F (10° to 32° C) | | | |
| Required Relative Humidity | 15% to 85% | | | |
| Sound Power Levels | Operating 7.1 B(A), Standby: 5.0 B(A) | | | |
| Sound Pressure Levels | Operating: 56 dB(A), Standby: 35 dB(A) | | | |
| Dimensions and Weight | Width | Depth | Height | Weight |
| Base Configuration with Internal Tray | 33.5 in. / 850 mm | 26.2 in. / 665 mm | 45.3 in. / 1,150 mm | 249 lbs. / 113 kg |
| With Office Finisher | 57.9 in. / 1,470 mm | 26.2 in. / 665 mm | 45.3 in. / 1,150 mm | 314.5 lbs. / 142.5 kg |
| With Office Finisher with Booklet Maker | 60.2 in. / 1,530 mm | 26.2 in. / 665 mm | 45.3 in. / 1,150 mm | 349.5 lbs. / 158.5 kg |
| Work Surface (does not add to overall width with Bypass Tray open) | 11.2 in. / 285 mm | - | - | - |

| Certifications | |
|--|--|
| | FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® GOST NOM Blue Angel ECOLOGO® CE Marked Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) EPEAT (United States) GS Mark Citrix® Certified WHQL MEDITECH Cerner To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . |
| Paper Handling | |
| Single-pass Automatic Document Feeder | |
| Capacity³ | 200 sheets |
| Speed (black-and-white and color) | Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex) black-and-white, up to 160 ipm (duplex) color |
| Paper Sizes Sensed | 4.9 x 5.4 in. to 11.7 x 17 in. / 125 x 138 mm to 297 x 432 mm |
| Weights | 13 lb. bond to 43 lb. bond / 50 gsm to 160 gsm |
| Bypass Tray | |
| Capacity³ | 100 sheets |
| Sizes | Custom sizes: 4.25 x 5.5 in. to 11 x 17 in. / A6 to A3 |
| Weights | 16 lb. bond to 80 lb. cover / 60 to 216 gsm |
| Types | Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled |
| Trays 1 and 2 | |
| Capacity³ | 500 sheets each |
| Sizes | Custom Sizes from 5.5 x 8.5 in. LEF to 11 x 17 in. SEF / A5 to A3 |
| Weights | 16 lb. bond to 53 lb. bond / 60 to 200 gsm |
| Types | Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Transparencies (Tray 2 only) |

Xerox® WorkCentre® 5945/5955

| Copy | |
|---------------------------------|--|
| First-copy-out Time | As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder |
| Sides (input:output) | 1-1, 1-2, 2-2, 2-1 |
| Quantity | 1 to 9,999 |
| Resolution (max.) | Scan: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi, 256 shades of gray |
| Reduction / Enlargement | Variable zoom from 25% to 400% in 1% increments |
| Concurrency | Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan) |
| Copy Features | <ul style="list-style-type: none"> Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services Auto Paper Select AutoReduction&Enlargement to fit selected paper size AutoTray Switching Automatic 2-sided / Duplex Booklet Creation BuildJob: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies |
| Xerox® Copier Assistant® | Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com |
| Print | |
| First-print-out Time | As fast as 7 seconds |
| Print Resolution | Up to 1200 x 1200 dpi, 256 shades of gray |
| Print Features | <ul style="list-style-type: none"> Application Defaults Banner Sheet Enable / Disable Bi-directional Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margin on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) |
| Print from USB | <ul style="list-style-type: none"> Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS®, PCL |
| Operating Systems | <ul style="list-style-type: none"> Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64 |

Xerox® WorkCentre® 5945/5955

| | |
|--|--|
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled |
| Administrative Protocols | DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP |
| Fonts | PCL: 93 scalable fonts, lineprinter and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts |
| Xerox® Mobile Express Driver® | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Xerox® Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. |
| Xerox® Pull Print Driver | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others. |
| Print Solutions | |
| Xerox® Mobile Print Cloud (Optional) | Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it. |
| Xerox® Mobile Print Solution (Optional) | Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment. |
| Unified Address Book | |
| Features | Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc. |
| Scan | |
| Concurrency | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs) |
| Input Speed | Scan at up to 160 ipm color scanning and 200 ipm black-and-white scanning – 8.5 x 11 in. / A4 LEF |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color) |
| Maximum Scan Area | 11 x 17 in. / A3 |
| Scan Template Management | Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options |
| Network Protocols | sFTP, FTP, SMB, NetWare, HTTP, HTTPS |
| File Compression | Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3MH, G4MMR, JBIG2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A |
| Document Management Fields (Meta Data) | Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input |
| Scan Features | Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10) |

| | |
|---|---|
| Scan to Email (Standard) | |
| Scan Features | <ul style="list-style-type: none"> • Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self |
| Directory Access | <p>Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino)</p> <p>Downloaded address list (comma-separated file format)</p> <p>Utilizes the Unified Address Book</p> |
| Scan to... (Standard) | |
| Features | <p>Scan to USB</p> <p>Scan to Network Folder (uses Unified Address Book entries)</p> |
| Network Scanning – Software Solutions | |
| Xerox® Scan to PC Desktop® Professional (Optional) | <p>A desktop offering that provides advanced document imaging, archiving, editing and organization tools:</p> <ul style="list-style-type: none"> • PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> - Complete PDF functionality - Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • ImageRetriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability |
| Xerox® ConnectKey® for SharePoint® (Optional) | <p>Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey Technology is the right solution for any office that needs to archive and share paper-based documents.</p> |
| Xerox® ConnectKey Share to Cloud (Optional) | <p>Xerox® ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, Salesforce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.</p> |
| Xerox® ConnectKey® for DocuShare® (Optional) | <p>Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).</p> |
| Security | |
| Features | <ul style="list-style-type: none"> • Expanded Authentication <ul style="list-style-type: none"> - Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP - Xerox® Secure Access - Local Authentication (internal database) - Smart Card authentication - 144k CAC / PIV Card Support (2048 bit certificate key) / .NET • Secure Data <ul style="list-style-type: none"> - Digitally signed PDF (when using Smart Card authentication) - Encrypted Scan to Email - Encrypted / Password Protected PDF (Email and Network Scan Templates only) - Secure Print (up to 10 digit PIN or Network Authentication) - Immediate Image Overwrite - On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk - FIPS 140-2 256 bit Hard Disk Encryption • Expanded Authorization <ul style="list-style-type: none"> - SA access based on network credentials - Authorization per user per service - User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver • Secure Network Access • IP Filter, IPsec, IPv6, SSLV3.0, SNMPV3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration (optional), Device Security <ul style="list-style-type: none"> - McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408 (undergoing evaluation) |
| Xerox Secure Access Unified ID System® (Optional) | <p>Xerox Secure Access Unified ID System integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job.</p> <p>For more information, go to www.office.xerox.com/software-solutions</p> |
| Fax | |
| Network Server Fax Features | |
| Compatibility | <p>ITY (CCITT) group 3</p> <p>Various Xerox® Business Innovation Partner Solutions</p> |
| Maximum Scan Area | 11 x 17 in. / A3 |
| Fax Send Features | <p>One- or two-sided scanning (up to 11 x 17 in. / A3)</p> <p>Add to send list (50 numbers maximum)</p> <p>Build Job, Favorites, Delay send (specific time) Original type (photo, text or photo and text)</p> |

Xerox® WorkCentre® 5945/5955

| | |
|---|---|
| Fax Print Features | One- or two-sided printing, staple, Secure Print |
| Transmission Resolution | Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi |
| Internet Fax Features | |
| Capability | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients |
| Address Directory Access | Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white) |
| Network Protocols | SMTP (send), POP3 (receive) |
| Compliance | ITU-T T.37 compliant |
| Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines) | |
| Compatibility | ITU (CCITT) Group 3 |
| Speed / Modems | One or Two V.34 modems: 33,600bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilizing T.38 (optional) |
| Compression / Speed | MH/G3, MMR/SG3 |
| Resolution | Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes |
| Fax Send Features | LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favorites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts) |
| Fax Receive Features | One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Up to 200 password protected mailboxes Secure receive Receive timestamp Auto answer delay |
| Fax Forward | Forward to Email or SMB Location Fax forward on receive only |
| Fax Reports | Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report |
| Auto Dialing | Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements) • 1 to 25 minute intervals • Batch send (up to memory capacity) |
| Device Management | |
| Management Support | SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2 |
| Xerox® CentreWare® Web | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView® |
| Novell NDPS/NEPS | Server gateway application: centralized management tool. |

| | |
|---|--|
| Xerox® Device Manager | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities |
| Xerox® Device Types for SAP Environment | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions |
| Xerox® SAP R/3 Intelligent Barcode Utility (optional) | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions |
| Xerox® Barcode Pro PS (optional) | Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions |
| CentreWare Internet Services – Integrated Web Pages Provided by the Device | |
| Device Status | Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts Remote Control Panel |
| Job Submission | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS®, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint) |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |
| Browsers | Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12 |
| Support | Install print / scan drivers and online support available via web page |
| Languages Supported | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese |
| Remote Services | |
| Xerox® MeterAssistant® | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. |
| Xerox® SuppliesAssistant® | Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. |
| Xerox® MaintenanceAssistant | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. |
| Accounting | |
| Xerox® Standard Accounting (Standard) | |
| Tracking | Copy, Print, Fax, Scan and Email usage |
| Accounting | Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department) |
| Features | <ul style="list-style-type: none"> • Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file |
| Accounting Options – Network Accounting – Third Party Enablement | |
| | <ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Business Innovation Partners. For details visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • WorkCentre requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface |



Xerox® WorkCentre® 5945/5955

| Supplies | Description | Quantity | Part Number |
|-------------------------------|--|--|------------------------|
| Toner Cartridge | Includes 2 Toner Cartridges | 88,000 pages ⁵ (44,000 pages each) ⁵ | 006R01604 |
| Toner Cartridge (sold) | Includes 2 Toner Cartridges | 88,000 pages ⁵ (44,000 pages each) ⁵ | 006R01605 |
| | Office Finisher with Booklet Maker – saddle-stitch stapling | 2,000 per cartridge (8,000 staples) | 108R01158 |
| | Convenience Stapler – Complete Cartridge – Refill Cartridge | 5,000 per cartridge 5,000 per cartridge (15,000 staples) | 008R12964 008R12941 |
| Smart Kits® | | | |
| Fuser Module | North America: Europe: | 350,000 ² 350,000 ² | 109R00847 109R00848 |
| Print Cartridge | Includes xerographic drums, developer module, including dual auger ring, toner dispense, toner concentration sensor, development roll, trim bar and developer material | 200,000 ³ | 013R00669 |

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ XPS option is required to print XPS files.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area cover and print mode.



✓ فرع الجيزة: 3 ش فهمي حجازي من ش حسن عبد العال - شارع فيصل

تليفون: 0111200645 - 339325880 - 33935881

✓ فرع هدينة نصر: 17 ش عبد الحكيم الرفاعي من ش عباس العقاد

تليفون: 01112000539 01112000568 - 26721839 - 26721840

✓ فرع اسكندرية: 25 ش احمد زكي ابو شادي - متفرع من ش المنارة - اهرام نادي وياه الاسكندرية

تليفون: 01211634446 - 01211634446 - 01211644005 - 4252158
012211644002 - 01211644470

Returns spent imaging supplies through the Xerox® GreenWorld Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call 1-800-ASK-XEROX or visit us at www.xerox.com/office.

